



## NAC3MPX-WOT-TOP

電源用レセプタクルコネクタ パワコン  
TRUE1TOPシリーズ パワーインレット 背面端子  
ガード無しモデル

powerCON TRUE1 (パワコン トゥルーワン) シリーズは大容量かつロック機構を備えた、高い信頼性を持つ3極電源コネクタです。オリジナルワンタッチロック機構、イージーアッセンブル、活線挿抜可能等の機能にご好評を頂き、幅広くお客様にお使い頂いております。

そのシリーズの後継として登場したのがpowerCON TRUE1 TOP(パワコン トゥルーワン トップ) シリーズです。従来品と互換性を持ちつつ、ゴムブッシング部分の紫外線耐性を高めました。

### 製品の特長

- ・背面端子ガード無し
- ・芯数：3
- ・定格電圧：250V ac
- ・定格電流：20A
- ・活線挿抜可
- ・適合ダストカバー：SCNAC-MPX

## Technical Information

Product	
Title	NAC3MPX-WOT-TOP

Electrical	
Contact resistance	$\leq 2 \text{ m}\Omega$
Dielectric strength	4 kVdc / 2.8 kVac
Insulation resistance	$> 1 \text{ G}\Omega$ (after damp heat test)
Number of electrical contacts	2 + PE
Rating Europe	EN 60320-1: 16 A 250 V AC
Rating USA	UL 498: 20 A 250 V AC

Mechanical	
Lifetime	$> 5000$ mating cycles
Wiresize	2.5 mm <sup>2</sup> または安全規格に則ったケーブル
Wiresize	12 AWG または安全規格に則ったケーブル

Material	
Contact plating	2 $\mu\text{m}$ Ag
Locking element	Stainless steel
Shell	Polyamide (PA 6.6)
Contacts	Spring Copper (CuSn0.2)

Environmental	
Flammability	UL 94 V-0
Protection class	IP65, UL50E enclosure type4 rating in combination with SCNAC-MPX (mated or with closed cap)
Temperature range	-30 °C to +80 °C
Solderability (for PCB)	Complies with IEC 68-2-20