



NC3FX-SPEC

FX-SPECシリーズは通常のラッチロックに加え、抜去防止用のロック機構を付けたコネクタです。

ハウジングを強固に接続できるためデジタル信号の伝送など、高周波ノイズ対策としても適しています。

Features & Benefits

XLRタイプメス型3ピンケーブルコネクター SPECタイプ

- ・コンタクト：金メッキ
- ・ハウジング：黒クロームメッキ
- ・ロック付き

Technical Information

Product	
Title	NC3FX-SPEC.
Connection Type	XLR
Gender	female

Electrical	
Capacitance between contacts	≤ 4 pF
Contact resistance	≤ 3 m Ω
Dielectric strength	1,5 kVdc
Insulation resistance	> 10 G Ω (initial)
Rated current per contact	16 A
Rated voltage	< 50 V

Mechanical	
Cable O.D.	3.5 - 8.0 mm
Insertion force	≤ 20 N
Withdrawal force	≤ 20 N
Lifetime	> 1000 mating cycles
Wiresize	max. 2.5 mm ²
Wiresize	max. 14 AWG
Wiring	Solder contacts
Locking device	Locking nut

Material	
Boot	Polyurethan
Contact plating	0.2 µm Au hard alloy over 2 µm Ni
Contacts	Bronze (CuSn6)
Insert	Polyamide (PA66)
Locking element	St3K32 (latch) / Ck 67 (spring)
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	Black chromium
Strain relief	Polyacetal (POM)
Securing Ring	Brass (CuZn39Pb3)

Environmental	
Approvals	UL
Flammability	UL 94 V-0
Standard compliance	IEC 61076-2-103
Protection class	IP 40
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C