NEUTRIK

NC3MD-LX

フルメタルハウジングを使用した高信頼性レセプタクルコネクター「ＤＬシリーズ」がさらに性能を高め「ＤＬＸシリーズ」へと生まれ変わりました。

より確かな接地を実現するための「２点接地仕様」を採用。また新設計のハウジングは特にＲＦノイズへの対策に向けられ、総合的に対ノイズ性能を飛躍的に改善。

次世代の幅広いアプリケーションに対応します。

Features & Benefits

XLRタイプオス型3ピンレセプタクルコネクター　DLXシリーズ　シルバー

・コンタクト：銀メッキ
・ハウジング：ニッケルメッキ

Technical Information

Product	
Title	NC3MD-LX
Connection Type	XLR
Gender	male

All rights reserved / 16.11.2026

NEUTRIK

Electrical	
Capacitance between contacts	≤ 4 pF
Contact resistance	≤ 5 mΩ
Dielectric strength	1,5 kVdc
Insulation resistance	> 10 GΩ (initial)
Rated current per contact	16 A
Rated voltage	< 50 V

Mechanical	
Insertion force	≤ 20 N
Withdrawal force	≤ 20 N
Lifetime	> 1000 mating cycles
Wiresize	max. 2.5 mm²
Wiresize	max. 14 AWG
Wiring	Solder contacts
Locking device	Latch lock
Chassis shape	D

Material	
Contact plating	2 µm Ag
Contacts	Brass (CuZn35Pb2)
Insert	Polyamide (PA66)
Locking element	Steel Ck67
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	Nickel

All rights reserved / 16.11.2026

Environmental	
Flammability	UL 94 V-0
Standard compliance	IEC 61076-2-103
Protection class	IP 40
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C

All rights reserved / 16.11.2026