



## NC3MPR-HD

MPR-HD (Heavy duty) シリーズはケーブルコネクタのX-HDシリーズと嵌合させることにより保護等級IP65を実現するレセプタクルコネクタです。

堅剛なその作りは屋外での使用や工業用途に最適です。

### Features & Benefits

XLRタイプオス型3ピンレセプタクルコネクター MPR-HDシリーズ

- ・ 保護等級IP65 : NC3FX-HD、NC3FX-HD-Bとの嵌合時に発揮
- ・ 保護等級IP67 : NC3FXX-HD-D、NC3FXX-HD-B-Dとの嵌合時に発揮
- ・ コンタクト : 金メッキ
- ・ハウジング : ニッケルメッキ
- ・ IEC 61984:2008準拠

## Technical Information

Product	
Title	NC3MPR-HD
Connection Type	XLR
Gender	male
Remark	Male connectors are not intended to be used as Input Connectors.

Electrical	
Capacitance between contacts	$\leq 4 \text{ pF}$
Contact resistance	$\leq 5 \text{ m}\Omega$
Dielectric strength	1,5 kVdc
Insulation resistance	$> 10 \text{ G}\Omega$ (initial)
Rated current per contact	16 A
Rated voltage	50 Vac
Over voltage category	I

Mechanical	
Insertion force	≤ 20 N
Withdrawal force	≤ 20 N
Lifetime	> 1000 mating cycles
Wiresize	1.5 – 2.5 mm <sup>2</sup>
Mechanical endurance	COC
Wiring	Solder contacts
Locking device	Latch lock
Mounting direction	Front mounting
Chassis shape	P

Material	
Contact plating	0.2 µm Au over 2 µm Ni
Contacts	Brass (CuZn39Pb3)
Insert	Polyamide (PA 6.6 30 % GR)
Locking element	Steel Ck67
Gasket	Tesnit®
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	Nickel

Environmental	
Flammability	UL 94 HB
Standard compliance	IEC 61076-2-103
Protection class according to IEC 60529	IP 65 - mated with HD cable connector NC3FX-HD*
	IP67 - mated with HD cable connector NC3FXX-HD*
Pollution degree according to IEC 60664-1	2
Solderability	Complies with IEC 60068-2-20
Temperature range	-30 °C to +80 °C
Maximum operating temperature	+40 °C