NEUTRIK

NC5FXX-B

プロオーディオのディファクトスタンダードコネクターとして世界中で広く、永くご愛用いただいた**X**シリーズコネクターが新しくなりました。

新シリーズ「**XX**シリーズ・ケーブルコネクター」では、旧シリーズの小さな不満のすべてを見直し、更に完成度を高めました。

Features & Benefits

XLRタイプメス型**5**ピンケーブルコネクター　ブラック

・コンタクト：金メッキ
・ハウジング：黒クロームメッキ
・最小限の部品点数でイージーアッセンブルを実現（ドライバー不要）

All rights reserved / 12.10.2024

NEUTRIK

Technical Information

Product	
Title	NC5FXX-B
Connection Type	XLR
Gender	female

Electrical	
Capacitance between contacts	≤ 7 pF
Contact resistance	≤ 3 mΩ
Dielectric strength	1,5 kVdc
Insulation resistance	> 10 GΩ (initial)
Rated current per contact	7,5 A
Rated voltage	< 50 V

Mechanical	
Cable O.D.	3.5 - 8.0 mm
Insertion force	≤ 20 N
Withdrawal force	≤ 20 N
Lifetime	> 1000 mating cycles
Wiresize	max. 1.0 mm²
Wiresize	max. 18 AWG
Wiring	Solder contacts
Locking device	Latch lock

All rights reserved / 12.10.2024

NEUTRIK

Material

Boot	Polyurethan
Contact plating	0.2 µm Au hard alloy over 2 µm Ni
Contacts	Brass (CuZn39Pb3)
Insert	Polyamide (PA66)
Locking element	Zinc diecast (ZnAl4Cu1) / Ck 67 (spring)
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	Black chromium
Strain relief	Polyacetal (POM)

Environmental

Flammability	UL 94 V-0
Standard compliance	IEC 61076-2-103
Protection class	IP 40
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C

All rights reserved / 12.10.2024