NEUTRIK

NF2C-B/2

ProFi（プロフィ）は、ノイトリック独自の画期的な機構を備えたハイレベル・ユーザー向け**RCA**オーディオプラグです。

従来のピンプラグが持つ宿命的欠点である接続時のノイズ発生を、コールド側を先に接触させるという方法で克服しました。

Features & Benefits

・コンタクト：金メッキ
・**L/R 2**個セット
・外径**3.0mm**～**7.3mm**のケーブルに対応（**CNF-9**を使用することで**8.0mm**まで対応可）

All rights reserved / 12.10.2024

NEUTRIK

Technical Information

Product	
Title	NF2C-B/2
Connection Type	Profi
Gender	male

Electrical	
Capacitance between contacts	≤ 7 pF
Contact resistance	>10G mΩ
Dielectric strength	1,5 kVdc
Insulation resistance	> 5 GΩ
Rated current per contact	depends on mating connector / A
Rated voltage	< 50 V

Mechanical	
Cable O.D.	3.0 - 7.3 mm
Lifetime	> 2000 mating cycles
Wiresize	1,5 mm²
Wiresize	16 AWG
Wiring	Solder contacts

All rights reserved / 12.10.2024

NEUTRIK

Material

Contact plating	5 µm Au over 5 µm Ni
Contacts	Brass (CuZn39Pb3)
Insert	PBTP 20 % GR
Shell	Brass (CuZn39Pb3)
Strain relief	Polyacetal (POM)

Environmental

Flammability	UL 94 HB
Standard compliance	IEC 601-14
Protection class	IP 40
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C

All rights reserved / 12.10.2024