



NKHDMI-*

The HDMI patch cables with overmolded flex relief and rugged metal cable carrier fit and lock with NAHDMI-W-*

The cables are available in 0.6 m, 1 m, 3 m, 5 m, 7 m, 8 m and 10 m cable length.

Neutrik's HDMI solution for the transmission of any digital TV and PC video format including high-definition video (HDTV) can be integrated in networks very easy.

Features & Benefits

- Data rate up to 18 GBit/s
- ケーブル長：1m、3m、5m、10mの4タイプ
- HDMI2.0対応（10mのNKHDMI-10のみ HDMI1.4）
- 対応するレセプタクルとの嵌合時には保護等級IP65を実現
- コネクタ一部分のボディは取り外し可能
- ボディを取り外すと弊社製レセプタクル以外のメスコネクタと接続可能となります)
- 受注生産品

Article Variants

Article name	Length	Order code
NKHDMI-0.6	0.6 m HDMI Cable with 2x Male HDMI Connector	NKHDMI-0.6
NKHDMI-1	1 m HDMI Cable with 2x Male HDMI Connector	NKHDMI-1
NKHDMI-3	3 m HDMI Cable with 2x Male HDMI Connector	NKHDMI-3
NKHDMI-5	5 m HDMI Cable with 2x Male HDMI Connector	NKHDMI-5
NKHDMI-7	7 m HDMI Cable with 2x Male HDMI Connector	NKHDMI-7
NKHDMI-8	8 m HDMI Cable with 2x Male HDMI Connector	NKHDMI-8
NKHDMI-10	10 m HDMI Cable with 2x Male HDMI Connector	NKHDMI-10

Technical Information

Product	
Title	NKHDMI-*
Gender	male

Mechanical	
Wiresize	
Minimum bending radius allowed	40 mm
Lifetime	> 1000 mating cycles
Locking device	Push-Pull
Overall cable diameter	6,5 mm

Material	
Contact plating	Au
Contacts	Bronze (CuSn)
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	Nickel
Cable jacket material	PVC

Environmental	
Flammability	UL 94 V-0
Standard compliance	HDMI 2.0 specifications for length up to 3 m incl. HDMI 1.4 specifications for length > 3 m
Temperature range	-25 °C to +85 °C