



NKHDMI-*

The HDMI patch cables with overmolded flex relief and rugged metal cable carrier fit and lock with NAHDMI-W-*

The cables are available in 0.6 m, 1 m, 3 m, 5 m and 10 m cable length.

Neutrik's HDMI solution for the transmission of any digital TV and PC video format including high-definition video (HDTV) can be integrated in networks very easy.

Features & Benefits

- Data rate up to 18 GBit/s
- ケーブル長：1m、3m、5m、10mの4タイプ
- HDMI2.0対応（10mのNKHDMI-10のみ HDMI1.4）
- 対応するレセプタクルとの嵌合時には保護等級IP65を実現
- コネクタ一部分のボディは取り外し可能
- ボディを取り外すと弊社製レセプタクル以外のメスコネクタと接続可能となります)
- 受注生産品

Technical Information

| Product | |
|---------|----------|
| Title | NKHDMI-* |
| Gender | male |

| Mechanical | |
|--------------------------------|----------------------|
| Wiresize | |
| Minimum bending radius allowed | 40 mm |
| Lifetime | > 1000 mating cycles |
| Locking device | Push-Pull |
| Overall cable diameter | 6,5 mm |

| Material | |
|-----------------------|-------------------------|
| Contact plating | Au |
| Contacts | Bronze (CuSn) |
| Shell | Zinc diecast (ZnAl4Cu1) |
| Shell plating | Nickel |
| Cable jacket material | PVC |

| Environmental | |
|---------------------|--|
| Flammability | UL 94 V-0 |
| Standard compliance | HDMI 2.0 specifications for length up to 3 m incl. HDMI 1.4 specifications for length > 3 m |
| Temperature range | -25 °C to +85 °C |