NEUTRIK

NP2RX-B

PRXシリーズは**90**度**L**型ボディのフォーンプラグです。

コンソール裏面など、狭い場所における結線や楽器用などに最適です。

PXシリーズ同様、そのスマートなデザインが人気の秘密です。

Features & Benefits

1/4"フォーンプラグ　**PRX**シリーズ　ブラック

・コンタクト：金メッキ
・ハウジング：黒**KTL**コーティング
・フォーンジャック仕様：モノラル
・対応ケーブル径：**4～7mm**
（**5.5mm**径以上のケーブルをお使いの場合は中のプラスティックパーツの一部を折ってお使い下さい。詳細は**Downloads**の**Assembly Instruction**のパート**D**をご参照下さい。）

Technical Information

Product	
Title	NP2RX-B
Connection Type	Plug
Gender	male

All rights reserved / 16.11.2026

NEUTRIK

Electrical	
Contact resistance	depends on mating connector mΩ
Dielectric strength	1 kVdc
Insulation resistance	> 2 GΩ (initial)
Rated current per contact	depends on mating connector A
Rated voltage	< 50 V

Mechanical	
Cable O.D.	4 - 7 mm
Lifetime	> 1000 mating cycles
Wiresize	1 mm²
Wiresize	18 AWG
Wiring	Solder contacts

Material	
Bushing	Polyacetal (POM) + PU
Contact plating	0.2 µm Au
Contacts	Brass (CuZn39Pb3)
Insert	Polyamide (PA 6.6 30 % GR)
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	KTL coating
Strain relief	Polyacetal (POM)

All rights reserved / 16.11.2026

Environmental	
Standard compliance	IEC 60603-11 / EIA RS-453
Solderability	Complies with IEC 68-2-20
Temperature range	-20 °C to +65 °C

All rights reserved / 16.11.2026