NEUTRIK

NP2X-B-CRYSTAL

* 生産終了品 *
流通在庫が無くなり次第販売終了となります。

クリスタルコンはスワロフスキー社とのコラボレーションにより実現しました。

ケーブルコネクターのハウジングにスワロフスキークリスタルを装飾し、ステージでの視覚効果向上に大きな力を発揮します。

Features & Benefits

・コンタクト：金メッキ
・ハウジング：黒クロームメッキ
・フォーンジャック仕様：モノラル
・対応ケーブル径：**4～7mm**
（**5.5mm**径以上のケーブルをお使いの場合は中のプラスティックパーツの一部を折ってお使い下さい。詳細は**Downloads**のフォーンプラグアッセンブルガイドをご参照下さい。）

Technical Information

Product	
Title	NP2X-B-CRYSTAL
Connection Type	Plug
Gender	male

All rights reserved / 30.04.2025

NEUTRIK

Electrical	
Contact resistance	depends on mating connector mΩ
Dielectric strength	1 kVdc
Insulation resistance	> 2 GΩ (initial)
Rated current per contact	depends on mating connector A
Rated voltage	< 50 V

Mechanical	
Cable O.D.	4 - 7 mm
Lifetime	> 1000 mating cycles
Wiresize	1 mm²
Wiresize	18 AWG
Wiring	Solder contacts

Material	
Bushing	Polyacetal (POM) + PU
Contact plating	0.2 µm Au
Contacts	Brass (CuZn39Pb3)
Insert	Polyamide (PA 6.6 30 % GR)
Shell	made with CRYSTALLIZED™ - Swarovski Elements
Shell plating	Black chromium
Strain relief	Polyacetal (POM)

All rights reserved / 30.04.2025

Environmental	
Standard compliance	IEC 60603-11 / EIA RS-453
Solderability	Complies with IEC 68-2-20
Temperature range	-20 °C to +65 °C

All rights reserved / 30.04.2025