NEUTRIK

NP2X-WT

PXシリーズは完全プロフェッショナル仕様の
フォーンプラグです。

音質、耐久性に優れ、他シリーズ同様チャック方式を採用しケーブルを確実にクランプします。

さらにはそのスマートなデザインに人気が集まっています。

Features & Benefits

1/4"フォーンプラグ　**X**シリーズ　ホワイト

・コンタクト：ニッケルメッキ
・ハウジング：ニッケルメッキ
・フォーンジャック仕様：モノラル
・対応ケーブル径：**4～7mm**
（**5.5mm**径以上のケーブルをお使いの場合は中のプラスティックパーツの一部を折ってお使い下さい。詳細は**Downloads**のフォーンプラグアッセンブルガイドをご参照下さい。）

Technical Information

Product	
Title	NP2X-WT
Connection Type	Plug
Gender	male

All rights reserved / 01.05.2025

NEUTRIK

Electrical	
Contact resistance	depends on mating connector mΩ
Dielectric strength	1 kVdc
Insulation resistance	> 2 (initial) GΩ ≥ 1 GΩ (after damp heat test)
Rated current per contact	depends on mating connector A
Rated voltage	< 50 V

Mechanical	
Cable O.D.	4 - 7 mm
Lifetime	> 1000 mating cycles
Wiresize	1 mm²
Wiresize	18 AWG
Wiring	Solder contacts

Material	
Bushing	Polyacetal (POM) + PU
Contact plating	2 µm Ni (Su)
Contacts	Brass (CuZn38Pb3)
Insert	Polyamdie (PA 6.6 30 % GR)
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	White painted
Strain relief	Polyacetal (POM)

All rights reserved / 01.05.2025

Environmental	
Standard compliance	IEC 60603-11 / EIA RS-453
Solderability	Complies with IEC 68-2-20
Temperature range	-20 °C to +65 °C

All rights reserved / 01.05.2025