# NP2X

**PX**シリーズは完全プロフェッショナル仕様の
フォーンプラグです。

音質、耐久性に優れ、他シリーズ同様チャック方式を採用しケーブルを確実にクランプします。

さらにはそのスマートなデザインに人気が集まっています。

## Features & Benefits

**1/4"**フォーンプラグ　**X**シリーズ　シルバー

・コンタクト：ニッケルメッキ
・ハウジング：ニッケルメッキ
・フォーンジャック仕様：モノラル
・対応ケーブル径：**4～7mm**
（**5.5mm**径以上のケーブルをお使いの場合は中のプラスティックパーツの一部を折ってお使い下さい。詳細は**Downloads**のフォーンプラグアッセンブルガイドをご参照下さい。）


All rights reserved / 12.10.2024

NEUTRIK

# Technical Information

| Product | |
|---|---|
| **Title** | NP2X |
| **Connection Type** | Plug |
| **Gender** | male |

| Electrical | |
|---|---|
| **Contact resistance** | depends on mating connector mΩ |
| **Dielectric strength** | 1 kVdc |
| **Insulation resistance** | > 2 (initial) GΩ ≥ 1 GΩ (after damp heat test) |
| **Rated current per contact** | depends on mating connector A |
| **Rated voltage** | < 50 V |

| Mechanical | |
|---|---|
| **Cable O.D.** | 4 - 7 mm |
| **Lifetime** | > 1000 mating cycles |
| **Wiresize** | 1 $mm^2$ |
| **Wiresize** | 18 AWG |
| **Wiring** | Solder contacts |


All rights reserved / 12.10.2024

NEUTRIK

## Material

| | |
|---|---|
| **Bushing** | Polyacetal (POM) + PU |
| **Contact plating** | 2 µm Ni (Su) |
| **Contacts** | Brass (CuZn39Pb3) |
| **Insert** | Polyamide (PA 6.6 30 % GR) |
| **Shell** | Zinc diecast (ZnAl4Cu1) |
| **Shell plating** | Nickel |
| **Strain relief** | Polyacetal (POM) |

## Environmental

| | |
|---|---|
| **Standard compliance** | IEC 60603-11 / EIA RS-453 |
| **Solderability** | Complies with IEC 68-2-20 |
| **Temperature range** | -20 °C to +65 °C |


All rights reserved / 12.10.2024