



NP3X-B

PXシリーズは完全プロフェッショナル仕様の
フォーンプラグです。

音質、耐久性に優れ、他シリーズ同様チャック方式
を採用しケーブルを確実にクランプします。

さらにはそのスマートなデザインに人気が集まっ
ています。

Features & Benefits

1/4"フォーンプラグ Xシリーズ ブラック

- ・コンタクト：金メッキ
- ・ハウジング：黒クロームメッキ
- ・フォーンジャック仕様：ステレオ
- ・対応ケーブル径：4~7mm

(5.5mm径以上のケーブルをお使いの場合は中のプラスチックパーツの一部を折ってお使い下さい。詳細はDownloadsのフォーンプラグアッセンブルガイドをご参照下さい。)

Technical Information

Product	
Title	NP3X-B
Connection Type	Plug
Gender	male

Electrical	
Contact resistance	depends on mating connector mΩ
Dielectric strength	1 kVdc
Insulation resistance	> 2 GΩ (initial)
Rated current per contact	depends on mating connector A
Rated voltage	< 50 V

Mechanical	
Cable O.D.	4 - 7 mm
Lifetime	> 1000 mating cycles
Wiresize	1 mm ²
Wiresize	18 AWG
Wiring	Solder contacts

Material	
Bushing	Polyacetal (POM) + PU
Contact plating	0.2 µm Au
Contacts	Brass (CuZn39Pb3)
Insert	Polyamide (PA 6.6 30 % GR)
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	Black chromium
Strain relief	Polyacetal (POM)

Environmental	
Standard compliance	IEC 60603-11 / EIA RS-453
Solderability	Complies with IEC 68-2-20
Temperature range	-20 °C to +65 °C